



A8 Tunable White. The power-pack A8 is now also available with white LEDs. It is equipped with 37 multi-chip LEDs in the 15W class. Each multi-chip LED has two cold-white and two warm-white chips, which allow continuous adjustment of the colour temperature from 2900 Kelvin to 7700 Kelvin.

The enormous light output of the A8 is achieved by a combination of highly efficient optics, maximum packing density of the LEDs and the most advanced LED cooling system developed so far.

Furthermore, it has a very mature software solution for LED control. Continuous dimming with different dimming curves is the basis for comfortable working. Different modes allow flicker-free working in TV studios.

The A8 Tunable White is controlled via DMX wiring or the radio module integrated ex-works in combination with the Wireless TRX by JB-Lighting. Compared to conventional white-light sources, the A8 Tunable White has the great advantage that it is very compact, efficient, easy to handle and power efficient. In addition, it produces little waste heat and is thus particularly pleasant as front light e.g. for bands or during fashion shows.

Optics and light source

- Zoom system 4°-48° (4°-33°, measured at 1/2 peak; 8°-48° measured at 1/10th peak)
- Highly efficient lens system
- 37 RGBW multichip LEDs in the 15W class, each carrying two warm white and two cold white chips
- Hexagonal lens form for high density packing and compact design



Tunable White

7700K

5600K

2900K

Effects

- 450° Pan / 330° Tilt
- Separate CTC channel
- High-resolution steplessly variable dimmer 0% -100%
- Flickerfree performance due to flex mode
- Electronic strobe with pulse and random effects

Movement

- High-resolution three-phase stepper motors
- Precise and fast movements
- Silent, ideal for noise-sensitive applications

Control

- DMX 512
- Integrated DMX-in module for JB-Lighting Wireless DMX
- Illuminated graphics display, can be rotated electronically
- Stand-alone mode

Power consumption

- 545W maximum

Construction

- Compact housing
- Powercon In and Out
- 3-pin und 5-pin XLR connectors
- Temperature-controlled fans
- Omega bracket for fast and comfortable mounting in every position
- Dimensions: w 359 x h 449 x d 265mm
- Weight: 11kg

Accessories

- Wireless TRX
- Omega-bracket for single clamp attachment
- Double flightcase
- Quad flightcase

JB LIGHTING

JB-Lighting Lichtenlagentechnik GmbH · Sallersteig 15 · D-89134 Blaustein
Tel. +49 7304 9617-0 · Fax +49 7304 9617-99
www.jb-lighting.de