



P-5 Wash Light

Specifications	Optics	Light source	44 x High power 10W RGBW LEDs
		LEDs expected lifetime	50,000 hours*
		Interchangeable lens option	15°, 21° & 43°
	Photometric	Light output	23,500 lumen (43° lens)
		Efficacy	58 lm/W
	Features	Pan/Tilt	+ / - 90°
	Electrical	AC Power	208 - 240 V Nominal 50/60 Hz
		Maximum power consumption	450 W (all LEDs on)
		Typical power consumption	420 W (all LEDs on)
		Power factor	0.98 PF (230 V)
	Programming and Control	Protocol	USITT DMX512 A
		Setting and addressing	Wireless DMX (LumenRadio) RDM Stand alone mode (programmable by RFID) Oled graphical display / 5 buttons Software upgradeable via Uploader cable (P/N:83062011)
		DMX channels	3, 4, 6, 8, 9 or 10
	Physical	Dimensions (L x H x W)	497 x 268 x 122 mm (19.6 x 10.6 x 4.8 in)
		Weight	8.9 kg (19.6 lbs.)
		Material	Aluminium
		Lens	PE and tempered glas front
		IP class	IP65 (fan module IP55)
	Installation	Mounting	Any, but facing 100% down for permanent installation
		Rigging possibilities	Floor stand (included) or hanging (Omega Clamps included)
		Safety features	Bottom mount for Safety wire
	Thermal	Temperature range, Operating	-10° – 40°C (-14° – 104°F)
		Temperature range, Start-up	-10° – 40°C (-14° – 104°F)
		Humidity (max.)	98%
		Cooling	Active, Forced air, temperature-regulated, low noise
	Connections	DMX data in/out	IP65 Neutrik HD locking XLR 5-pin cable 0.5m, for DMX in and out Power cable 0.5m with bare ends
	Certified to Conforms to	CSA Std. C22.2 No. 166	
		UL Std. 1573	
		2006/95/EC: Low Voltage Directive 2004/108/EC: EMC Directive	EN 60598-1, EN 60598-2-17, EN 62471 EN 55103-1, EN 55103-2, EN 61000-3-2, EN 61000-3-3
	Included Items	Included Items	Floor Stand (incl. screws) 2 pcs Omega Clamps Wireless DMX G4 antenna User manual Neopren pouch
	Fixtures and Accessories	Fixtures	Order no: 80030507 - P-5 Wash Light (43°) Order no: 80030501 - P-5 Wash Light (21°) Order no: 80030508 - P-5 Wash Light (15°)
		Lens/s	Order no: 83061104 - P-5, Lens kit (43°) Order no: 83061103 - P-5, Lens kit (21°) Order no: 83061102 - P-5, Lens kit (15°)
		Brackets	Order no: 83060603 - BCC-2 Dual bracket Order no: 83060604 - BCC-4 Quad bracket
		Floorstand	Order no: 83060610 - Floorstand for P, Q and X series with 1/4-turn fasteners
		Barndoor	Order no: 83061119 - Accessory Holder P Series Order no: 83061120 - Barndoor 4-way Order no: 83061121 - Barndoor 8-way Order no: 83061122 - Color frame
		Cables	Order no: 83062011 - SGM USB uploader cable
		Flight case	Order no: 82051501 - Flight case for 4 pcs of P-5/Q-7/X-5

*(Figure provided by manufacturer and obtained under manufacturer's test conditions)