



Q-2 RGBW Color Flood Blind Strobe Light

Specifications		
Optics	Light source	864 x RGBW SMD LEDs (5,700K)
	LEDs expected lifetime	50,000 hours*
Photometric	Lens options	110° fixed
	Light output	12,000 lumen
Features	Efficacy	60 lm/W
	Pan/Tilt	0° / 180°
Electrical	LED Panel	3 individual controllable segments
	AC Power nominal	100 - 240 V 50/60 Hz
	AC Power max rating	90-264V 50/60Hz
	Maximum power consumption	275 W (all LEDs on)
Programming and Control	Typical power consumption	200 W (all LEDs on)
	Power factor	0.98 PF (230 V)
	Protocol	USITT DMX512 A
	Setting and addressing	RDM Stand alone mode Oled graphical display / 4 buttons Software upgradable via Uploader cable (P/N:83062011)
	DMX channels	1, 3, 6, 12, 15 or 22
Physical	Dimensions (L x H x W)	334 x 223 x 105 mm (13,2 x 8,8 x 4.1 in)
	Weight	6,0 kg (13,2 lbs.)
	Material	Aluminium
	Lens	Tempered glas front
	IP class	IP65
Installation	Orientation	Any
	Rigging possibilities	Floor stand (included) or hanging (Omega Clamp included)
	Safety features	Bottom mount for Safety wire
Thermal	Temperature range, Operating	-10° to +40°C (-14° to +104°F)
	Humidity (max.)	98%
	Cooling	Active, forced air, temperature-regulated, low noise
Connections	DMX data in/out	IP65 Neutrik HD locking XLR 5-pin cable 0.5m, for DMX in and out Power cable 1m with bare ends
	Certification	2006/95/EC: Low Voltage Directive 2004/108/EC: EMC Directive
Included Items		EN60598-1, EN60598-2-17, EN62471 EN55103-1, EN55103-2, EN61000-3-2, EN61000-3-3
	Included Items	Floor Stand (incl. screws) 1 pcs Omega Clamp User manual Neopren pouch
Fixtures and Accessories	Fixtures	Order no: 80030535 - Q-2 Color Flood Light
	Cables	Order no: 83062011 - SGM USB uploader cable

*(Figure provided by manufacturer and obtained under manufacturer's test conditions)