

## **Q-7 W** White wash blind strobe

Specifications	Optics	Light source	1,000 x Cool White LEDs (5,700K)
		LEDs expected lifetime	50,000 hours*
		Lens	110° fixed
	Photometric	Links autous	CO 000 lumas
	Photometric	Light output Efficacy	60,000 lumen 130 lm/W
		CRI	Min. 75
	Features	Pan/Tilt	+ / - 90°
		LED Panel	Four individual controllable panels
	Electrical	AC Power	208 - 250 V Nominal 50/60 Hz
		Maximum power consumption	485 W (all LEDs on)
		Typical power consumption	455 W (all LEDs on)
		Power factor	0.99 PF (230 V)
	Programming and Control	Protocol	USITT DMX 512 A
	0	Setting and addressing	Wireless DMX (LumenRadio)
			RDM
			Stand alone mode (programmable by RFID)
			Oled graphical display / 5 buttons Software upgradeable via Uploader cable (P/N:83062011)
		DMX channels	4, 6 or 8
	Physical	Dimensions (L x H x W)	497 x 268 x 122 mm (19.6 x 10.6 x 4.8 in)
		Weight	8.1 kg (17.9 lbs.)
		Material Lens	Aluminium Tempered glas front
		IP class	IP65 (fan module IP55)
	Installation	Mounting	Any, but facing 100% down for permanent installation
		Rigging possibilities	Stand bracket (included) or hanging (Omera Clamps included)
		Safety features	Bottom mount for Safety wire
	Thermal	Temperature range, Operating	-10° - 40°C (-14° - 104°F)
		Temperature range, Start-up	-10° - 40°C (-14° - 104°F)
		Humidity (max.)	98%
		Cooling	Active, Forced air, temperature-regulated, low noise
	Connections	DMX data in/out	IP65 Neutrik HD locking XLR 5-pin cable 0.5m, for DMX in and out
		Power	Power cable 0.5m with bare ends
	Contification	FIL Cofety.	EN COEGO 2 47 (EN 2000 4) EN C2474
	Certification	EU Safety EU EMC	EN 60598-2-17 (EN20698-1), EN 62471 EN 55 015, EN 55 103-1
		LO LINO	2.1.55 525, 2.11 55 105 1
	Included Items	Included Items	Floor Stand (incl. screws)
			2 pcs Omega Clamps
			Wireless DMX G4 antenna User Manual
			Neopren pouch
	Fixtures and Accessories	Fixtures	Order no: 80030504 - Q-7 W White flood light
		Brackets	Order no: 83060603 - BCC-2 Dual bracket
		Floorstand	Order no: 83060604 - BCC-4 Quad bracket Order no: 83060610 - Floorstand for P, Q and X series with 1/4-turn fasteners
		Barndoor	Order no: 83061123 - Accessory Holder X & Q Series
			Order no: 83061120 - Barndoor 4-way
			Order no: 83061121 - Barndoor 8-way
		Calalan	Order no: 83061122 - Color frame
		Cables Flight case	Order no: 83062011 - SGM USB uploader cable Order no: 82051501 - Flight case for 4 pcs of P-5/Q-7/X-5
	*(Figure provided by manufacturer	-	

<sup>\*(</sup>Figure provided by manufacturer and obtained under manufacturer's test conditions)