F22 series

High-performance single-chip DLP projector with 1080p, SXGA+ or WUXGA resolution up to 3,300 lumens



The F22-series is the ultimate compact performance projector for technically challenging and demanding applications. Providing world-class technology, a functional and innovative design, the F22 delivers an unmatched level of performance, reliability, automation and customization.

The design is in the details

Featuring WUXGA, 1080p and SXGA+ resolutions with up to 3,300 lumens, the F22 ensures the best possible result for your image needs in every situation. Its compact footprint makes smart use of valuable installation area and reduces the resources required during physical installation. Once mounted, lamp changes can be done with the projector in situ, saving both time and money.

Performance you can count on The F22-series projectors are specifically engineered for demanding environments such as motion-based simulators or theme park rides, where reliability and performance are paramount. Each projector is manufactured and meticulously tested and calibrated in the Barco center of excellence in Norway. The product is warranted for 24/7 operation and is supported around-the-clock by Barco's global service and support team.



Product specifications F22 series

Technology	single-chip DLP® projector
Concept	optical lens shift design
3D capability	INFITEC EX® 3D
Resolution	SXGA+ (1,400 x 1,050) / 1080p (1,920 x 1,080) / WUXGA (1,920 x 1,200)
Brightness	Up to 3,300 lumens
Contrast	Up to 2,500 : 1 (Nominal full field on/off)
Aspect ratio	16:9 (720p) / 4:3 (SXGA+) / 16:9 (1080p) / 16:10 (WUXGA)
Display colors	Less than 1 Billion colours, 30-bit RGB
Latency	~22ms frame on graphics port
Computer graphics formats	1,920 x 1,200 - 640 x 480 pixel resolution (model dependent) / RGBHV, RGBS, RGsB
Horizontal scan frequencies	15 - 150 kHz (resolution dependant)
Vertical scan frequencies	48 - 190 Hz (resolution dependant)
Video formats	EDTV (576p, 480p) / SDTV (576i, 480i) / HDTV (1080p, 1080i, 720p) /NTSC, PAL, SECAM
Lens operation	Focus, shift and manual zoom
Lenses	 Wide Angle EN17 lens - throw ratios: 1.09 : 1 (720p) / 1.00 : 1 (SXGA+) / 0.92 : 1 (1080p) / 0.92 : 1 (WUXGA) Ultra Wide Angle EN19 lens - throw ratios: 0.88 : 1 (720p) / 0.80 : 1 (SXGA+) / 0.74 : 1 (1080p) / 0.74 : 1 (WUXGA) Short Tele Zoom EN32 lens - throw ratios: 2.96 - 4.62 : 1 (720p) / 2.71 - 4.22 : 1 (SXGA+) / 2.50 - 3.90 : 1 (1080p) / 2.50 - 3.90 : 1 (WUXGA) Standard projection lens EN35 - throw ratios: 1.89 - 2.62 : 1 (720p) / 1.73 - 2.39 : 1 (SXGA+) / 1.60 - 2.21 : 1 (1080p) / 1.60 - 2.21 : 1 (WUXGA) F22 lenses are not interchangeable
Image width	0.7 - 2.5 m
Light source	220W UHP lamp
Lamp lifetime	Up to 2,250 hours (full power) / up to 3,000 hours (Eco mode)
Computer inputs	1 x HDMI 1.3a, 1 x DVI-I, 1 x VGA
Video Input	1 x HDMI 1.3a, 1 x DVI-I, 1 x S-video, 1 x Composite, 1 x YPbPr
Control possibilities	TXTIBINI 1.56, TX BYTT, TX 5 YIGCO, TX COMPOSICE, TX TI BIT
Dimensions	1 x RI-45 TCP /IP 1 x 9-nin D-SHR RS232 1 x HSR
DIIIIGIISIOIIS	1 x RJ-45 TCP/IP, 1 x 9-pin D-SUB RS232, 1 x USB
	278 x 94 x 234 mm (WxHxD)
Weight	
Weight Shipping Dimensions	278 x 94 x 234 mm (WxHxD) 2.9 kg 440 x 440 x 31 mm (WxHxD)
Weight Shipping Dimensions Shipping Weight from Factory	278 x 94 x 234 mm (WxHxD) 2.9 kg 440 x 440 x 31 mm (WxHxD) 7.4 kg
Weight Shipping Dimensions	278 x 94 x 234 mm (WxHxD) 2.9 kg 440 x 440 x 31 mm (WxHxD) 7.4 kg 3.0-1.3A, ~100-240V, 50-60Hz
Weight Shipping Dimensions Shipping Weight from Factory Power requirements Conformances	278 x 94 x 234 mm (WxHxD) 2.9 kg 440 x 440 x 31 mm (WxHxD) 7.4 kg
Weight Shipping Dimensions Shipping Weight from Factory Power requirements Conformances Operating temperature	278 x 94 x 234 mm (WxHxD) 2.9 kg 440 x 440 x 31 mm (WxHxD) 7.4 kg 3.0-1.3A, ~100-240V, 50-60Hz CE, FCC Class A and cCSAus
Weight Shipping Dimensions Shipping Weight from Factory Power requirements Conformances Operating temperature Storage temperature	278 x 94 x 234 mm (WxHxD) 2.9 kg 440 x 440 x 31 mm (WxHxD) 7.4 kg 3.0-1.3A, ~100-240V, 50-60Hz CE, FCC Class A and cCSAus 10 - 40 °C
Weight Shipping Dimensions Shipping Weight from Factory Power requirements Conformances Operating temperature Storage temperature Operating humidity	278 x 94 x 234 mm (WxHxD) 2.9 kg 440 x 440 x 31 mm (WxHxD) 7.4 kg 3.0-1.3A, ~100-240V, 50-60Hz CE, FCC Class A and cCSAus 10 - 40 °C -20 - 60 °C
Weight Shipping Dimensions Shipping Weight from Factory Power requirements Conformances Operating temperature Storage temperature	278 x 94 x 234 mm (WxHxD) 2.9 kg 440 x 440 x 31 mm (WxHxD) 7.4 kg 3.0-1.3A, ~100-240V, 50-60Hz CE, FCC Class A and cCSAus 10 - 40 °C -20 - 60 °C 20 - 80% RH 10 - 90% RH
Weight Shipping Dimensions Shipping Weight from Factory Power requirements Conformances Operating temperature Storage temperature Operating humidity Storage humidity	278 x 94 x 234 mm (WxHxD) 2.9 kg 440 x 440 x 31 mm (WxHxD) 7.4 kg 3.0-1.3A, ~100-240V, 50-60Hz CE, FCC Class A and cCSAus 10 - 40 °C -20 - 60 °C 20 - 80% RH
Weight Shipping Dimensions Shipping Weight from Factory Power requirements Conformances Operating temperature Storage temperature Operating humidity Storage humidity Color	278 x 94 x 234 mm (WxHxD) 2.9 kg 440 x 440 x 31 mm (WxHxD) 7.4 kg 3.0-1.3A, ~100-240V, 50-60Hz CE, FCC Class A and cCSAus 10 - 40 °C -20 - 60 °C 20 - 80% RH 10 - 90% RH Black metallic 3 years standard warranty, 500 hours or 90 days on lamp (whichever comes first).



