

G-Profile Module

Specifications	Gobos	Outside diameter	37,5 mm
		Maximum image diameter	32 mm
		Maximum thickness	1.1 mm black&white or 3.5 mm colored glass
		Glass gobo	Borosilicate high temperature glass
		Metal gobo	Not recommended
	Features	Iris	1-100%, Pulse effects
		Dimming	Electronic
		Strobe	Ultra-high-speed strobe effect (1-50Hz)
		Gobo wheels	1 rotatable gobo wheels: 5 indexable gobos + open
		Framing	Rotatable framing module, +/- 45°,
		Effect wheel	4 controllable shutter blades, individually adjustable +/- 30° Effect wheel, continuous rotation with variable speed and direction
	Physical	Weight	3.9 kg (8.6 lbs.)
		Material	Aluminium, Steel, Plastic
	Approvals and Certifications	EMC Directive*	2004/108/EC EN 55103-1, EN 55103-2, EN61000-3-2, EN61000-3-3
		Low Voltage Directive*	2006/95/EC EN 60598-2-17, EN60598-1
	RoHS2 Directive	2011/65/EU	
Included Items	Included items	Framing module for G-Spot User manual	
Fixtures and Accessories	Fixtures	Order no: 83061405 - Framing module for G-Spot	

* Only when installed inside a G-Spot or G-Profile.