

G-Spot Module

Specifications	Gobos	Outside diameter	37,5 mm
		Maximum image diameter	32 mm
		Maximum thickness	1.1 mm black&white or 3.5 mm colored glass
		Glass gobo	Borosilicate high temperature glass
		Metal gobo	Not recommended
	Features	Iris	1-100%, Pulse effects
		Dimming	Electronic
		Strobe	Ultra-high-speed strobe effect (1-50Hz)
		Gobo wheels	2 independent rotatable gobo wheels: Gobo wheel 1: 5 indexable gobos + open Gobo wheel 2: 5 indexable gobos + open
		Effect wheels	2 independent effect wheels with Semi-continuous effect
	Physical	Weight	3.6 kg (7.9 lbs.)
		Material	Aluminium, Steel, Plastic
	Approvals and Certifications	EMC Directive*	2004/108/EC EN 55103-1, EN 55103-2, EN61000-3-2, EN61000-3-3
		Low Voltage Directive*	2006/95/EC EN 60598-2-17, EN60598-1
		RoHS2 Directive	2011/65/EU
	Included Items	Included items	Effect module for G-Profile User manual
Fixtures and Accessories	Fixtures	Order no: 83061407 - Effect module for G-Profile	

* Only when installed inside a G-Spot or G-Profile.