

### Lumen Radio CRMX transmitter DMX (Only)

Specifications		
Electrical	Power input	9V DC, 3.5mm center positive
	Power supply input	90-264VAC 50/60Hz
	Power supply output	9V DC
User interface	User interface	Pushbutton (link)
	DMX channels	512
Programming and Control	Protocol	CRMX
Physical	Dimensions	Length: 113 mm (4.4 in.)
		Width: 66 mm (2.6 in.)
		Height: 40 mm (1.6 in.)
	Weight	0,2 kg (0,44 lbs.)
Material	Aluminium, Plastic	
IP class	IP20	
Installation	Orientation	Any
Thermal	Temperature range	0°C - 40°C (32°F - 104°F)
	Cooling	Passive
Connections	Power input	9V DC, 3.5mm center positive
	Antenna connector	RP-TNC female
	DMX data out	Neutrik 5 pin XLR male
	Power supply input	EMS-US, EMS-UK, EMS-EU, EMS-AU and EMS-CC connector
	Power supply output	3.5mm center positive
Conforms to	2006/95/EC: Low Voltage Directive	EN 60950-1
	1999/5/EC: R&TTE Directive	ETSI EN 301489-1, ETSI EN 301489-3, ETSI EN300328, EN61547
	RoHS Directive	2011/65/EU
Conforms to (Power supply)	CCC, CE, cULus, GS, PSE	
	RoHS Directive	2011/65/EU
Included Items	Included items	2dB RP-TNC male antenna 9V DC power supply
Fixtures	Fixtures	Order no: 80070229 - Lumen Radio CRMX transmitter DMX (Only)
	Cables	Order no: 83062011 - SGM USB uploader cable