

## i-5 UV

### LED Wash Light

Specifications		
Optics	Light source	203 LEDs in total UV 203 pcs
	LEDs expected lifetime	50,000 hours*
	Lens option	8.5°
	Honeycomb	Optional
Features	Tilt	0 - 190°
Electrical	AC Power nominal	208 - 240 V Nominal 50/60 Hz
	Maximum power consumption	450 W (all LEDs on)
	Typical power consumption	420 W (all LEDs on)
	Power factor	0.98 PF (230 V)
Programming and Control	Protocol	USITT DMX512 A
	Setting and addressing	RDM Stand alone mode Oled graphical display / 4 buttons Software upgradable via Uploader cable (P/N:83062011)
	DMX channels	1, 2
Physical	Dimensions (L x H x W)	497 x 268 x 122 mm (19.6 x 10.6 x 4.8 in)
	Weight	8.9 kg (19.6 lbs.)
	Material	Aluminium
	Lens	PE and tempered glas front
	IP class	IP65
	Color options	White – RAL 9010 Black – RAL 9004 Custom color – any RAL
Installation	Orientation	Any
	Rigging possibilities	Floor stand (included) or hanging (Omega Clamp included)
	Safety features	Bottom mount for Safety wire
Thermal	Temperature range, Operating	-10° to +40°C (14° to +104°F)
	Temperature range, Start-up	-10° to +40°C (14° to +104°F)
	Humidity (max.)	98%
	Cooling	Active, forced air, temperature-regulated, low noise
Connections	DMX data in/out	IP65 Neutrik HD locking XLR 5-pin cable 0.5m, for DMX in and out
	Power	Power cable 1m with bare ends
Conforms to	2014/35/EU: Low Voltage Directive	EN 60598-1, EN 60598-2-17, EN 62471, EN 60529
	2014/30/EU: EMC Directive	EN 55103-1, EN 55103-2, EN 55015, EN 61547, EN 61000-3-2, EN 61000-3-3
	RoHS2 Directive	2011/65/EU
Included Items	Included Items	Floor Stand (incl. screws) 2 pcs Omega bracket Wireless DMX G4 antenna User manual
Fixtures and Accessories	Fixtures	Order no: 80031306 - i-5 UV Wash, 8,5deg, Std, BL Order no: 80031316 - i-5 UV Wash, 8,5deg, Std, BL, HC Order no: 80031356 - i-5 UV Wash, 8,5deg, Std, WH Order no: 80031366 - i-5 UV Wash, 8,5deg, Std, WH, HC Order no: 80031386 - i-5 UV Wash, 8,5deg, Std, CU Order no: 80031396 - i-5 UV Wash, 8,5deg, Std, CU, HC
	Cables	Order no: 83062011 - SGM USB uploader cable
	Bracket	Order no: 83060602 - Omega bracket Order no: 83060603 - BCC-2 Dual bracket Order no: 83060604 - BCC-4 Quad bracket
	Barndoor	Order no: 83060610 - Floorstand for P, Q and X series with 1/4-turn fasteners Order no: 83061119 - Accessory Holder P-5 Series Order no: 83061120 - Barndoor 4-way, P-5, X-5 & Q-7 Series Order no: 83061121 - Barndoor 8-way, P-5, X-5 & Q-7 Series Order no: 83061122 - Color frame, P-5, X-5 & Q-7 Series
	Flight case	Order no: 82051501 - Flight case for 4 pcs of P-5/Q-7/X-5 Order no: 82051502 - Flight case for 4 pcs of P-5/Q-7/X-5 incl. Barndoors

\*Photometrics / SGM Illumination Lab

Figures provided by manufacturer and obtained under manufacturer's test conditions

BL = Black (RAL 9004)

WH = White (RAL 9010)

CU = Custom Color (Any RAL color)

HC = Including Honeycomb